## POWER AMPLIFIER 2x240 W

## **UP2240D**

cod. 1400-224020









## TECHNICAL SPECIFICATIONS

Input sensitivity ±385mV, balanced input

Balanced inputs impedance  $20 \mbox{K}\Omega$ 

Frequency response (-3dB) 80  $\div$  16KHz (+1, -3dB) THD  $\leq$ 0,1% a 1KHZ, 1/3 of rated power

 Overload source
 >1 ldB

 Signal/noise ratio
 ≥85 dB

 Rating power RMS
 2x240W

 Power I.H.F.
 2x360W

 Speaker outputs, constant imp.
 4-16 Ω

 Speaker outputs, constant volt.
 100V

Protections overheating, overload, short circuit
Signal Led signal, peak protection, power

 Power supply from AC mains
 230Vac - 50Hz

 Power consumption
 650VA

 Dimensions (WxHxD)
 484x300x44mm

 Colour
 black

 Weight
 4,5Kg

Monophonic class D power amplifier, 2x240W. It features: one balanced input and one output for loudspeakers line, on extractable clamps. Through slip switch it is possible to select the output type (100V or 4-160hm). Additional output clamp for contact "amplifier fault". On the frontal part there are some led lights for signal: signal, peak, protection, power. Electronically-controlled forced ventilation cooling. Practical frontal control knob for volume level adjustment. Mains voltage power supply 230Vac - 50÷60Hz

Metallic case already set for rack installation. Size: 1 r.u.

AUDIO | ITC 67 POWER UNITS