

# 10W COLUMN SPEAKER

CS2 / T10

cod. 1900-142101



10W line array wall speaker with excellent voice quality in applications with reverb problems (churches, conference rooms, etc.). Aluminium extruded body with painted metal grille, provided with adjustable brackets for easy and quick wall-mount. Complete with line transformer with selectable power for better adjustment of sound level.

## TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	10W
Intermediate power	10/5W
Transformer impedance	1/2KΩ
Frequency response	170 + 15000Hz
S.P.L. 1W@1m	88 +3dB
Speaker type	2 x 2,5" full range
Speaker impedance	4Ω
IP protection degree	40
Dimensions	106x262x75mm
Fixing	no. 2 L-brackets
Material	aluminium
Colour	white
Weight	1,4Kg

## CONNECTION



NERO / BLACK COM  
VERDE / GREEN 2W  
BIANCO / WHITE 10W

# 20W COLUMN SPEAKER

CS4 / T20

cod. 1900-144201



20W line array wall speaker with excellent voice quality in applications with reverb problems (churches, conference rooms, etc.). Aluminium extruded body with painted metal grille, provided with adjustable brackets for easy and quick wall-mount. Complete with line transformer with selectable power for better adjustment of sound level.

## TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	20W
Intermediate power	20/10W
Transformer impedance	0,5/1KΩ
Frequency response	170 + 15000Hz
S.P.L. 1W@1m	91 +3dB
Speaker type	4 x 2,5" full range
Speaker impedance	4Ω
IP protection degree	40
Dimensions	106x405x75mm
Fixing	no. 2 L-brackets
Material	aluminium
Colour	white
Weight	2,0Kg

## CONNECTION



NERO / BLACK COM  
VERDE / GREEN 10W