

30W COLUMN SPEAKER

CS6 / T30

cod. 1900-146301



30W line array wall speaker with excellent voice quality in applications with reverb problems (churches, conference rooms, etc.). Aluminium extruded body with painted metal grille, provided with adjustable brackets for easy and quick wall-mount. Complete with line transformer with selectable power for better adjustment of sound level.

TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	30W
Intermediate power	30/15W
Transformer impedance	0,333/0,666K Ω
Frequency response	170 + 15000Hz
S.P.L. 1W@1m	92 +3dB
Speaker type	6 x 2,5" full range
Speaker impedance	4 Ω
IP protection degree	40
Dimensions	106x548x75mm
Fixing	no. 2 L-brackets
Material	aluminium
Colour	white
Weight	2,8Kg

CONNECTION



NERO / BLACK
VERDE / GREEN

COM
15W

40W COLUMN SPEAKER

CS8 / T40

cod. 1900-148401



40W line array wall speaker with excellent voice quality in applications with reverb problems (churches, conference rooms, etc.). Aluminium extruded body with painted metal grille, provided with adjustable brackets for easy and quick wall-mount. Complete with line transformer with selectable power for better adjustment of sound level.

TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	40W
Intermediate power	40/20W
Transformer impedance	0,25/0,5K Ω
Frequency response	170 + 15000Hz
S.P.L. 1W@1m	93 +3dB
Speaker type	8 x 2,5" full range
Speaker impedance	4 Ω
IP protection degree	40
Dimensions	106x690x75mm
Fixing	no. 2 L-brackets
Material	aluminium
Colour	white
Weight	3,5Kg

CONNECTION



NERO / BLACK
VERDE / GREEN

COM
20W