

20W VIBRATION SPEAKER

DTV / T20

cod. 1900-200202



20W VIBRATION SPEAKER

DTV / T20SE

cod. 1900-400202



20W VIBRATION SPEAKER

DTV / P

cod. 4300-200202



AB+SOUND is a speaker which produces the sound by not adding visible devices to the environment. It can voice entire stiff surfaces of different materials, making them vibrate and turn them into great acoustic propagators for background music, sound messages, call systems and so on. Therefore, it will be possible to make false ceilings, walls, windows, furniture, kitchen counters, tables and boat walls sound; this will make the sound-broadcasting much more captivating and enjoyable, regardless where the listener is.

It is a true revolution of the sound-broadcasting concept; it offers many advantages, given by the solution versatility, its neatness and invisibility, the installation ease, the homogeneity and the acoustic quality. AB+SOUND is a great aesthetic solution because it replaces the traditional speakers. Moreover, it works according to the principle of the flat diaphragm, transforming every surface in a "loudspeaker cone". It is easy and quick to install because there is no need of holes, you just stick it to the involved surface. AB+SOUND is also "green", because it can serve bigger spaces compared to the traditional speakers, for equal sound-broadcasting, considerably decreasing the electricity consumption. Available in passive version (with or without waterproof shell), 100V version (for standard or EVAC systems) and with Bluetooth receiver/amplifier.

TECHNICAL SPECIFICATIONS

Operating voltage	100V
RMS power	20W
Transformer impedance	4 Ω
Technology	magnetodynamic
Dimensions	168x139x36mm
Connection	screw terminal
IP protection degree	55
Fixing	included 3M sticker / 3 screws
Operating temperature	0°C + 80°C
Material	PC/ABS
Weight	540g

TECHNICAL SPECIFICATIONS

Operating voltage	100V
RMS power	20W
Transformer impedance	4 Ω
Technology	magnetodynamic
Dimensions	168x139x36mm
Connection	double screw terminal
IP protection degree	55
Fixing	included 3M sticker / 3 screws
Operating temperature	0°C + 80°C
Material	PC/ABS
Weight	540g

TECHNICAL SPECIFICATIONS

RMS power	20W
Transformer impedance	4 Ω
Technology	magnetodynamic
Dimensions	168x139x36mm
Connection	screw terminal
IP protection degree	55
Fixing	included 3M sticker / 3 screws
Operating temperature	0°C + 80°C
Material	PC/ABS
Weight	200g