

## 30W HORN SPEAKER

**DT24 / T30**

cod. 1900-285303



## 20W HORN SPEAKER

**DT20 / T20**

cod. 1900-284203



## 10W HORN SPEAKER

**DT14 / T10**

cod. 1900-283103



30W, 20W, 10W horn speaker for excellent quality of voice announcements in applications that require high sound. ABS body, round shape, provided with adjustable U-bracket for easy wall mount. Complete with line transformer with selectable power for better adjustment of sound level.

### TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	30W
Intermediate power	30/15/7.5/3.75W
Transformer impedance	0,333/0,666/1,333/2,666K $\Omega$
Frequency response	330 + 8000Hz
S.P.L. 1W@1m	118dB
Speaker type	magnetodynamic unit
Speaker impedance	20 $\Omega$
IP protection degree	64
Dimensions	$\phi$ 237mm x 290mm
Fixing	U-bracket
Material	ABS
Colour	grey
Weight	2,6Kg

### TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	20W
Intermediate power	20/10/5/2.5W
Transformer impedance	0,5/1/2/4K $\Omega$
Frequency response	250 + 8000Hz
S.P.L. 1W@1m	114dB
Speaker type	magnetodynamic unit
Speaker impedance	20 $\Omega$
IP protection degree	64
Dimensions	$\phi$ 198mm x 258mm
Fixing	U-bracket
Material	ABS
Colour	grey
Weight	1,9Kg

### TECHNICAL SPECIFICATIONS

Type	wall
Operating voltage	100V
RMS power	10W
Intermediate power	10/5/2,5W
Transformer impedance	1/2/4K $\Omega$
Frequency response	400 + 8000Hz
S.P.L. 1W@1m	107dB
Speaker type	magnetodynamic unit
Speaker impedance	16 $\Omega$
IP protection degree	64
Dimensions	$\phi$ 138mm x 207mm
Fixing	U-bracket
Material	ABS
Colour	grey
Weight	1,4Kg