

20W VIBRATION SPEAKER

DTV / BT20

cod. 1900-600202



20W VIBRATION SPEAKER

TRSD20W

cod. 4300-200203



AB+SOUND is a speaker which produces the sound by not adding visible devices to the environment. It can voice entire stiff surfaces of different materials, making them vibrate and turn them into great acoustic propagators for background music, sound messages, call systems and so on. Therefore, it will be possible to make false ceilings, walls, windows, furniture, kitchen counters, tables and boat walls sound; this will make the sound-broadcasting much more captivating and enjoyable, regardless where the listener is.

It is a true revolution of the sound-broadcasting concept; it offers many advantages, given by the solution versatility, its neatness and invisibility, the installation ease, the homogeneity and the acoustic quality. AB+SOUND is a great aesthetic solution because it replaces the traditional speakers. Moreover, it works according to the principle of the flat diaphragm, transforming every surface in a "loudspeaker cone". It is easy and quick to install because there is no need of holes, you just stick it to the involved surface. AB+SOUND is also "green", because it can serve bigger spaces compared to the traditional speakers, for equal sound-broadcasting, considerably decreasing the electricity consumption. Available in passive version (with or without waterproof shell), 100V version (for standard or EVAC systems) and with Bluetooth receiver/amplifier.

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--------------------------------|
| Operating voltage | 12Vdc (power supply included) |
| RMS power | 20W |
| Transformer impedance | 4 Ω |
| Technology | magnetodynamic |
| Dimensions | 168x139x36mm |
| Connection | Bluetooth |
| IP protection degree | 55 |
| Fixing | included 3M sticker / 3 screws |
| Operating temperature | 0°C + 80°C |
| Material | PC/ABS |
| Weight | 200g |

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--------------------------------|
| RMS power | 20W |
| Transformer impedance | 4 Ω |
| Technology | magnetodynamic |
| Dimensions | 168x139x36mm |
| Connection | screw terminal |
| Fixing | included 3M sticker / 3 screws |
| Operating temperature | 0°C + 80°C |
| Material | ABS |
| Weight | 200g |