

20W WALL SPEAKER

DP2512 / P

B cod. 4300-251201
N cod. 4300-251202
G cod. 4300-251203



Passive wall-mount speaker for excellent playback quality of voice announcements and background music. Polycarbonate self-extinguishing body in class V2. Available in: white, black and grey. Two different versions: 6W and 10W.

TECHNICAL SPECIFICATIONS

Type	wall-projecting
RMS power	20W
Frequency response	120 + 18000Hz
S.P.L. 1W@1m	93dB
Speaker type	4" bicone
Speaker impedance	4Ω
Dimensions	250x120x73mm
Max. protrusion	73mm
Material	ABS
Colour	white, black, grey
Weight	0,9Kg

20W PROJECTOR WALL SPEAKER

PS / P

cod. 4300-271201



Passive unidirectional 20W speaker for excellent quality of voice announcements in applications that require high efficiency in the maximum emission direction. It reduces reverb due to reflection of back and lateral walls, floor and ceiling. ABS body with painted metal grille, provided with adjustable U-bracket for easy simple and quick wall mounting. Suitable for covered and outdoor installations.

TECHNICAL SPECIFICATIONS

Type	wall
RMS power	20W
Frequency response	130 + 15000Hz
S.P.L. 1W@1m	92 +3dB
Speaker type	5" full range
Speaker impedance	8Ω
IP protection degree	65
Dimensions	ø137mm x 200mm
Fixing	U-bracket
Material	ABS
Colour	white
Weight	1,6Kg

20W HORN SPEAKER

DT1812 / P

cod. 4300-281103



Passive 20W horn speaker for excellent quality of voice announcements in applications that require high efficiency. ABS body with painted metal grille, provided with adjustable U-bracket for easy simple and quick wall mounting. Suitable for covered and outdoor installations.

TECHNICAL SPECIFICATIONS

Type	wall
RMS power	20W
Frequency response	400 + 20000Hz
S.P.L. 1W@1m	106dB
Speaker type	magnodynamic unit
Speaker impedance	20Ω
IP protection degree	64
Dimensions	180x116x232mm
Fixing	U-bracket
Material	ABS
Colour	grey
Weight	1,8Kg