BOX 503 RECESSED MICROPHONE

MI503

cod. 3200-231000





★ Civil series → p. 97



High-sensitivity electret cardioid microphone that guarantees excellent voice quality in situations where the speaker is distant from the microphone.

To combine with A20/5 amplified power supply.

Microphone capsule and preamplifier circuit mounted on vetronite support with adhesive lexan, suitable for installation in 3-module box that is taken completely.

Available in multiple civil series. Weight: 0.09 Kg.

BOX 503 RECESSED SPEAKER

DI503 / H

cod. 6400-103000





*** Civil series** → p. 97



Small-size speaker for installation in box 503 that is taken completely. The size of the loudspeaker permits a power of 3 W. Indicated for those rooms where there are space problems.

Equipped with CA10MP amplifier module to be housed separately. Available in multiple civil series.

TECHNICAL SPECIFICATIONS

 Input impedance
 10ΚΩ

 Output level
 3Vpp

 Frequency response
 100*15000Hz

 Power supply
 12Vdc

 Absorption
 50mA

 Microphone type
 electrete

 Material
 metal

TECHNICAL SPECIFICATIONS

 RMS power
 3W

 Frequency response
 220+2000Hz

 Impedance
 8 Ω

 Loudspeaker type
 fullrange

 Material
 metal

MEGA RSA 74 ITC | GRMS