

PROXIMITY CARD READER

LTC-T

B cod. 6700-113001
N cod. 6700-113002



13.56MHz Mifare proximity card reader, with capacitive glass touch panel. Enables differentiated access to room for guests, staff, managers, maintenance operators, etc. Features “bell” button and icons signally “guest in room”, “do not disturb”, “check mini-bar” and “room to be cleaned”. Also signals “valid card”, “invalid card” and “alarm in progress”. Housed in 3 modules flush mounting box. Connection to UGC-IP unit and other units or panels via RJ12 connector for transmission of data and for 12Vdc power supply. Dimensions 127x95x9mm (+44mm internal). Weight 0.2 Kg. Colour: black, white

PROXIMITY CARD READER FOR COMMON AREAS

LTZ-T

B cod. 6700-117001
N cod. 6700-117002



13.56MHz Mifare proximity card reader, with capacitive glass touch panel. Allows differentiated access to shared spaces for guests, staff, managers, maintenance operators, etc. Features “bell” button and relay output with volt-free contact for electronic ringtone or opening contact (max. 24V, 4(2) A). Housed in 3 modules flush mounting box. Connection to UGT-IP unit and other units or panels via RJ12 connector for transmission of data and for 12Vdc power supply. Dimensions 127x95x9mm (+44mm internal). Weight 0.2 Kg. Colour: black, white