

SMART ROOM ACTIVATOR

AIT-T

B cod. 6700-125001
N cod. 6700-125002



Detects the presence in the room of guest or staff via proximity card in slot and activates the room's facilities only if the card has been enabled. Capacitive glass touch panel with illuminated slot for card. Features buttons for "room service", "do not disturb" and "housekeeping". Housed in 3 modules flush mounting box. Connection to UGC-IP unit and further units or panels via RJ12 connector for transmission of data and for 12Vdc power supply. Dimensions 127x95x9mm (+44mm internal). Weight 0.2 Kg. Colour: black, white

TEMPERATURE CONTROL PANEL

PTF-T

B cod. 6700-133001
N cod. 6700-133002



Capacitive glass touch panel for managing air conditioning, with integrated temperature sensor. Allows the guest to change temperature, speed, automatic or manual functioning mode and to shut down the air conditioning system. The display shows the set temperature, the actual temperature, speed, functioning mode, windows status and alarm messages (help request, overflow, breaking). The panel allows staff to reset alarms locally and set "room cleaned" and "mini-bar replenished" messages. Housed in 3 modules flush mounting box. Connected to UGC-IP, UGT-IP and UGF units via RJ12 connector for transmission of data and for 12Vdc power supply. Alternatively, may be supplied directly via specific 12Vdc, 3.5A power supply unit. Dimensions 127x95x9mm (+44mm internal). Weight 0.2 Kg. Colour: black, white