

SMART HANDLE

ME

G cod. 6800-101010
N cod. 6800-101011



Good-looking, extremely safe and remotely controllable. It is the new smart handle which can be mounted on internal doors and it is suitable for self-check in facilities. Built with use-resistant materials and, therefore, long-lasting. EASYOPEN is a design product, perfect to get balanced with any décor style, easily mountable also on already existing doors. For operating, the handle needs 4pcs AA batteries. It has a strengthened mechanics compared to other similar products for private residences and it is specifically studied for professional installations in accommodation facilities, where the mechanical stress is higher. Moreover, there is the possibility to manage it from far away on any device, thanks to the control and access App, designed for both iOS and Android devices. Available also in total black.

TECHNICAL SPECIFICATIONS

Material	zinc, stainless steel and ABS alloy
Available colours	grey, black
Communication	bluetooth 4.0 BLE
Operating system compatibility	iOS 7.0 or higher – Android 4.4 or higher
Battery duration	10.000 openings
Opening ways	RFID cards, numerical pin code, APP, mechanical key
Unlock time	1 + 1,5 seconds
Operating temperature	-20°C + +40°C
Operating humidity	10% - 95%
IP protection degree	IP62
Wi-fi gateway	available
Packaging	cardboard, expanded polyethylene
Dimensions	230x75x80 mm
Door thickness (mm)	min. 38 – max. 55
Max. number of cards	150
Max. number of pin codes	150

OUTDOOR KEYBOARD

TN

cod. 6800-101020



In combination with the indoor handles, this wall keyboard makes an entire facility completely self-check-in because it allows to control all the openings located before the rooms: gates, residents front door, garages, etc. It can also be applied in extra hotel contexts, such as work places, sports buildings, churches and all the locations where an access control is needed. Suitable to any type of opening, a simple or an armoured door, a shutter, a barrier, a gate, etc. The device is set up for wall installation and, through the output contact, it drives the electric strike or the electric lock which opens the opening. Designed and produced to resist to any weather and to be installed in any place: being equipped with backlit keyboard, it is simple to locate even at night or in little lit places. It has the same functions and opening ways as the smart handle. It has got: output for door opening, output for ring bell, input for door opening internal button and input for door status (opened or closed). It can be mounted in a vertical box 503.

TECHNICAL SPECIFICATIONS

Material	aluminium, glass
Colour	grey
Communication	bluetooth 4.1
Operating system compatibility	iOS 7.0 or higher – Android 4.3 or higher
Power supply	12Vdc
Stand-by power	15mA
Operating power	1A
Opening ways	RFID cards, numerical pin code, APP, mechanical key
Unlock time	1 + 1,5 seconds
Operating temperature	-20°C + +40°C
Operating humidity	10% - 95%
IP protection degree	IP66
Wi-fi gateway	available
Packaging	cardboard, expanded polyethylene
Dimensions	125x15,5x79mm
Max. number of cards	2000
Max. number of pin codes	2000